

Family Design Series

312		Battery Capacity: 12000mAh(44.4Wh) Size: 186x98x37mm Weight: 590g Peak Current: 1800A	Input: USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
313		Battery Capacity: 16000mAh(59.2Wh) Size: 244x105x32mm Weight: 745g Peak Current: 2500A	Input: USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) 15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
322		Battery Capacity: 24000mAh(88.8Wh) Size: 245x105x41mm Weight: 898g Peak Current: 3250A	
333		Battery Capacity: 16000mAh(59.2Wh) Size: 223x93x38mm Weight: 620g Peak Current: 2500A	Input: USB-C 5V/3A Output: Quick charge(5V/3A;9V/2A;12V/1.5A) 5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
351		Battery Capacity: 24000mAh(88.8Wh) Size: 252x98x57mm Weight: 1.09kg Peak Current: 3250A	Input: USB-C PD100W(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD100W(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A) 5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
536		Battery Capacity: 10000mAh(37Wh) Size: 175x87x36mm Weight: 430g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
240		Battery Capacity: 16000mAh(59.2Wh) Size: 224x89.6x36mm Weight: 625g Peak Current: 2500A	Input: USB-C 15W(5V/3A) Output: 5V/2.4A;Quick charge(5V/2.4A;9V/2A;12V/1.5A) USB-C 15W(5V/3A;15V/10A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
241		Battery Capacity: 24000mAh(88.8Wh) Size: 224x89.6x43.8mm Weight: 775g Peak Current: 3250A	Input: USB-C15W(5V/3A) Output: 5V/2.4A;Quick charge(5V/2.4A;9V/2A;12V/1.5A) USB-C 15W(5V/3A;15V/10A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
528		Battery Capacity: 10000mAh(37Wh) Size: 164x84x35mm Weight: 420g Peak Current: 1500A	Input: USB-C 5V/2.4A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
600		Battery Capacity: 24000mAh(88.8Wh) Size: 223x84x35mm Weight: 750g Peak Current: 3250A	Input: USB-C 5V/2.4A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

AC Series

183		Battery Capacity: 18000mAh(66.6Wh) Size: 224x101x34mm Weight: 830g Peak Current: 2750A AC Output:100W	Input: USB-C 9V/2A Output: Quick charge(5V/3A;9V/2A;12V/1.5A) 15V/10A; 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
316		Battery Capacity: 62500mAh(225Wh) Size: 238x103x98mm Weight: 2.17kg Peak Current: 1100A AC Output:120W	Input: USB-C PD/SC100W Max(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD100W Max(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A); 5V/2.4A; 15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

Waterproof Series

535		Battery Capacity: 10000mAh(37Wh) Size: 184x95x31mm Weight: 505g Peak Current: 1500A IP Rating: IP65	Input: USB-C 15W 5V/3A Output: USB1+USB2 5V/3.4A; USB-C 15W 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
533		Battery Capacity: 10000mAh(37Wh) Size: 188x93x35.5mm Weight: 540g Peak Current: 1500A IP Rating: IP65	Input: USB-C 15W 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 15W 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
590		Battery Capacity: 12000mAh(44.4Wh) Size: 177x87x38mm Weight: 550g Peak Current: 1800A	Input: USB-C PD65W Output: USB-C PD65W; Quick charge(5V/3A;9V/2A;12V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
298		Battery Capacity: 20000mAh(74Wh) Size: 235x90x42mm Weight: 992g Peak Current: 3000A IP Rating: IP65	Input: USB-C PD/SC 65W (5V/3A;9V/3A;12V/3A;15V/3A;20V/3.25A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD65W (5V/3A;9V/3A;12V/3A;15V/3A;20V/3.25A); 5V/2.4A; 15V/10A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
317		Battery Capacity: 24000mAh(88.8Wh) Size: 238x105x53mm Weight: 990g Peak Current: 3250A IP Rating: IP64	Input: USB-C PD/SC 100W Max(5V/3A;9V/3A;12V/3A;15V/3A;20V/5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD100W Max(5V/3A;9V/3A;12V/3A;15V/3A;20V/5A);15V/10A;5V/2.4A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

Super Capacitor Series

93C		Battery Capacity: 300Fx5 Size: 250x120x50mm Weight: 1.15kg Peak Current: 800A	Input: 5V/3A;12V/5A Output: 12V jump starter Operating Temp: -40°C~55°C Cycle Life: >100,000 times
161 (12V&24V)		Battery Capacity: 600Fx10 Size: 295x220x111mm Weight: 2.65kg Peak Current: 1200A	Input: 5V/3A Also suitable for 5V-1A/2A Output: 12V&24V jump starter Operating Temp: -40°C~55°C Cycle Life: >100,000 times
109A		Battery Capacity: 720Fx5 Size: 295x219x81mm Weight: 2kg Peak Current: 1200A	Input: 5V/2A;12V/10A Output: 12V jump starter Operating Temp: -40°C~55°C Cycle Life: >100,000 times

* All the data is from our laboratory, the design technical parameters and the suppliers. The actual data will be slightly affected by the software version, the use environment, temperature, vehicle horsepower, battery voltage and other factors.
The product structure picture is a functional diagram, not an absolute actual structure, and ultimately the actual object shall prevail.

Advantage-01



DSLI-IV Patent Core Technology,
Leading the industry

Quicker, More Powerful and Safer

Advantage-02



Full Coverage of
All Vehicles Types

From compact car to heavy duty truck, Instant start without worries

Advantage-03



10 Intelligent Protections,
Safety Guarding

safety guarding in 360°

Advantage-04



Extremely low power consumption,
No fear of battery drain

Still working ,even after storage of 2 Years

12&24V Series

395B		Battery Capacity: 36400mAh (134.7Wh) Size: 252x150x188.8mm Weight: 2.92kg Peak Current: 2800A	Input: USB-C (5V/2A; 9V/2A); DC 29V/5A Output: 5V/2.4A; 5V/1A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: ≥2000 times
326B		Battery Capacity: 56000mAh(207.2Wh) Size: 260.7x188x148.7mm Weight: 2.8kg Peak Current: 3500A	Input: 29V/2A Output: Quick charge(5V/3A;9V/2A;12V/1.5A) 12V/10A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: >1000 times
393B		Battery Capacity: 136500mAh (499.59Wh) Size: 295.5x175.5x245.4mm Weight: 5.4kg Peak Current: 7000A	Input: USB-C (5V/2A; 9V/2A); DC 29V/5A Output: 5V/2.4A; 5V/1A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: ≥2000 times
396D		Battery Capacity: 176000mAh (566.72Wh) Size: 340x222.5x263mm Weight: 8.34kg Peak Current: 4000A	Input: USB-C (5V/2A; 9V/2A); DC 29V/5A Output: 5V/2.4A; 5V/1A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: ≥2000 times

Sodium-ion series

625		Battery Capacity: 10400mAh(31.2Wh) Size: 224x89.6x43.8mm Weight: 650g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
627		Battery Capacity: 22400mAh(67.2Wh) Size: 266x239x119mm Weight: 2.5kg Peak Current: 3000A	Input: 5V/2A;9V/2A Output: 5V/2.1A;Quick charge (5V/3A;9V/2A); 12V/10A;12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
628		Battery Capacity: 13200mAh(39.6Wh) Size: 227x128x51mm Weight: 1.5kg Peak Current: 2000A Max Inflation Pressure: 150PSI	Input: 5V/2A;9V/2A Output: Quick charge (5V/3A;9V/2A); 12V/10A;12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
633		Battery Capacity: 12000mAh(36Wh) Size: 230x112.5x124mm Weight: 1.7kg Peak Current: 1800A Max Inflation Pressure: 160PSI	Input: PD30W Output: PD30W/QC 18W 12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
617N		Battery Capacity: 38400mAh(115.2Wh) Size: 277x126x156mm Weight: 3kg Peak Current: 4000A	Input: PD65W Output: 5V/2.4A; 12V/10A; 12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times

Economic Series

601		Battery Capacity: 10000mAh(37Wh) Size: 170x81x32mm Weight: 500g Peak Current: 1500A	Input: USB-C 5V/2.4A Output: USB1 5V/1A;USB2 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
613		Battery Capacity: 7500mAh(27.75Wh) Size: 158x85.8x27.6mm Weight: 353g Peak Current: 1200A	Input: USB-C 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A); 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
520A		Battery Capacity: 8000mAh(29.6Wh) Size: 148x82x29.5mm Weight: 320g Peak Current: 1200A	Input: USB-C 5V/2A Output: 5V/2A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
378B		Battery Capacity: 8000mAh(29.6Wh) Size: 151x80x29mm Weight: 326g Peak Current: 1200A	Input: USB-C 5V/2A Output: 5V/2.1A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
501		Battery Capacity: 10000mAh(37Wh) Size: 168x86x38.5mm Weight: 400g Peak Current: 1500A	Input: USB-C 5V/2A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
522		Battery Capacity: 10000mAh(37Wh) Size: 175x87x36mm Weight: 450g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A USB-C 5V/3A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

LFP series

617B		Battery Capacity: 64000mAh(204.8Wh) Size: 277x126x156mm Weight: 3.59kg Peak Current: 3400A	Input: USB-C PD 65W Output: USB 5V/2.4A;12V/10A;12V&24V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
78F		Battery Capacity: 32000mAh(102.4Wh) Size: 292x233x79mm Weight: 2.7kg Peak Current: 3000A	Input: 15V/1A Output: 5V/1A;5V/2A;12V/10A;12V&24V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
532F		Battery Capacity: 10000mAh(32Wh) Size: 172x89x34mm Weight: 480g Peak Current: 2200A	Input: 5V/2A Output: USB1+USB2 5V/3.4A Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
609		Battery Capacity: 12000mAh(38.4Wh) Size: 148x82x36mm Weight: 480g Peak Current: 2400A	Input: USB-C 5V/2A Output: USB-C 5V/2.1A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
507HF		Battery Capacity: 10000mAh(32Wh) Size: 122.2x164.2x46mm Weight: 711g Peak Current: 2200A	Input: 5V/2A Output: 5V/2.1A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
577F		Battery Capacity: 10000mAh(32Wh) Size: 197x120x56mm Weight: 850g Peak Current: 2200A	Input: 5V/2A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times

530		Battery Capacity: 10000mAh(37Wh) Size: 175x90x34mm Weight: 460g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
531		Battery Capacity: 10000mAh(37Wh) Size: 175x89x36mm Weight: 450g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
538		Battery Capacity: 10000mAh(37Wh) Size: 173.3x80x36mm Weight: 430g Peak Current: 1500A	Input: USB-C 5V/2.4A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
568		Battery Capacity: 10000mAh(37Wh) Size: 197x90.5x34.5mm Weight: 455g Peak Current: 1500A	Input: USB-C 15W 5V/3A Output: USB1 5V/1A; USB2 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
580		Battery Capacity: 12000mAh(44.4Wh) Size: 180.5x91x37mm Weight: 560g Peak Current: 1800A	Input: USB-C 5V/3A Output: USB-C PD45W;USB-A 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
510		Battery Capacity: 12000mAh(44.4Wh) Size: 190x85.8x39mm Weight: 520g Peak Current: 1800A	Input: USB-C 15W 5V/3A Output: USB1+USB2 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
529		Battery Capacity: 20000mAh(74Wh) Size: 218x85x39mm Weight: 660g Peak Current: 3000A	Input: USB-C 5V/2.4A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
386		Battery Capacity: 16000mAh(59.2Wh) Size: 225x89x30mm Weight: 564g Peak Current: 2500A	Input: USB-C 15W 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A) USB-C 15W 5V/3A;5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
387		Battery Capacity: 16000mAh(59.2Wh) Size: 224x87x39mm Weight: 540g Peak Current: 2500A	Input: USB-C 15W 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A) USB-C 15W 5V/3A;5V/2.4A;15V/10A12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
163D		Battery Capacity: 20000mAh(74Wh) Size: 225x91x34mm Weight: 750g Peak Current: 3000A	Input: Quick charge(5V/2A;9V/2A) Output: 5V/1A;5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
332		Battery Capacity: 24000mAh(88.8Wh) Size: 220x102x41mm Weight: 780g Peak Current: 3250A	Input: USB-C 15W 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A) 5V/2.4A; 15V/10A; USB-C 15W 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

Air Inflator Series

507		Battery Capacity: 10000mAh(37Wh) Size: 122.2x164.2x46mm Weight: 670g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.1A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
557		Battery Capacity: 10000mAh(37Wh) Size: 123x166x50mm Weight: 714g Peak Current: 1500A Max Inflation Pressure: 150PSI Battery Capacity: 10000mAh(37Wh) Size: 207x120x58mm Weight: 870g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.1A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
382		Battery Capacity: 10000mAh(37Wh) Size: 200x116x54mm Weight: 830g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
383		Battery Capacity: 10000mAh(37Wh) Size: 208x112x40mm Weight: 520g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
638		Battery Capacity: 10000mAh(37Wh) Size: 208x112x40mm Weight: 520g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
506		Battery Capacity: 12000mAh(44.4Wh) Size: 204x122.5x58mm Weight: 1kg Peak Current: 1800A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
615		Battery Capacity: 10000mAh(37Wh) Size: 220x127x58mm Weight: 1kg Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
325		Battery Capacity: 16000mAh(59.2Wh) Size: 223x123x63mm Weight: 1.5kg Peak Current: 2500A Max Inflation Pressure: 160PSI	Input: USB-C 9V/2A Output: 15V/10A; Quick charge (5V/3A;9V/2A;12V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
558A		Battery Capacity: 24000mAh(88.8Wh) Size: 230x112.5x124mm Weight: 1.7kg Peak Current: 3250A Max Inflation Pressure: 160PSI	Input: USB-C PD30W (5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Output: USB-C PD30W (5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Quick charge (5V/3A;9V/2A;12V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
558B		Battery Capacity: 12000mAh(44.4Wh) Size: 230x112.5x124mm Weight: 1.3kg Peak Current: 1800A Max Inflation Pressure: 150PSI	Input: USB-C 5V/3A Output: USB-A 5V/2.4A Operating Temp: -20°C~60°C Cycle Life: >1000 times
605		Battery Capacity: 10000mAh(37Wh) Size: 124x220x52.5mm Weight: 850g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.1A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
612		Battery Capacity: 9000mAh(33.3Wh) Size: 226x74.5x40mm Weight: 470g Peak Current: 1500A Motor Power: 300W MAX Fan battery life: 92Min MAX	Input: USB-C 10W (5V/2A) Output: USB 5V/2.1A Operating Temp: -20°C~60°C Cycle Life: >1000 times Gear Settings: 4 levels (Low, Medium, High, Turbo) Fan Speed: 50 m/s MAX