

Advantage-01



DSLI-IV Patent Core Technology, Leading the industry

Quicker, More Powerful and Safer

Advantage-02



Full Coverage of All Vehicles Types

From compact car to heavy duty truck, Instant start without worries

12&24V Series

395B		Battery Capacity: 36400mAh (134.7Wh) Size: 252x150x188.8mm Weight: 2.92kg Peak Current: 2800A	Input: USB-C (5V/2A; 9V/2A); DC 29V/5A Output: 5V/2.4A; 5V/1A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: ≥2000 times
326B		Battery Capacity: 56000mAh(207.2Wh) Size: 260.7x188x148.7mm Weight: 2.8kg Peak Current: 3500A	Input: 29V/2A Output: Quick charge(5V/3A;9V/2A;12V/1.5A) 12V/10A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: >1000 times
393B		Battery Capacity: 136500mAh (499.59Wh) Size: 295.5x175.5x245.4mm Weight: 5.4kg Peak Current: 7000A	Input: USB-C (5V/2A; 9V/2A); DC 29V/5A Output: 5V/2.4A; 5V/1A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: ≥2000 times
396D		Battery Capacity: 176000mAh (566.72Wh) Size: 340x222.5x263mm Weight: 8.34kg Peak Current: 4000A	Input: USB-C (5V/2A; 9V/2A); DC 29V/5A Output: 5V/2.4A; 5V/1A 12V&24V jump starter Operating Temp: -40°C~60°C Cycle Life: ≥2000 times

Sodium-ion series

625		Battery Capacity: 10400mAh(31.2Wh) Size: 224x89.6x43.8mm Weight: 650g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
627		Battery Capacity: 22400mAh(67.2Wh) Size: 266x239x119mm Weight: 2.5kg Peak Current: 3000A	Input: 5V/2A;9V/2A Output: 5V/2.1A;Quick charge (5V/3A;9V/2A); 12V/10A;12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
628		Battery Capacity: 13200mAh(39.6Wh) Size: 227x128x51mm Weight: 1.5kg Peak Current: 2000A Max Inflation Pressure: 150PSI	Input: 5V/2A;9V/2A Output: Quick charge (5V/3A;9V/2A); 12V/10A;12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
633		Battery Capacity: 12000mAh(36Wh) Size: 230x112.5x124mm Weight: 1.7kg Peak Current: 1800A Max Inflation Pressure: 160PSI	Input: PD30W Output: PD30W/QC 18W 12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times
617N		Battery Capacity: 38400mAh(115.2Wh) Size: 277x126x156mm Weight: 3kg Peak Current: 4000A	Input: PD65W Output: 5V/2.4A; 12V/10A; 12V jump starter Operating Temp: -40°C~80°C Cycle Life: >1000 times

LFP series

617B		Battery Capacity: 64000mAh(204.8Wh) Size: 277x126x156mm Weight: 3.59kg Peak Current: 3400A	Input: USB-C PD 65W Output: USB 5V/2.4A; 12V/10A;12V&24V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
78F		Battery Capacity: 32000mAh(102.4Wh) Size: 292x233x79mm Weight: 2.7kg Peak Current: 3000A	Input: 15V/1A Output: 5V/1A;5V/2A;12V/10A;12V&24V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
532F		Battery Capacity: 10000mAh(32Wh) Size: 172x89x34mm Weight: 480g Peak Current: 2200A	Input: 5V/2A Output: USB1+USB2 5V/3.4A Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
609		Battery Capacity: 12000mAh(38.4Wh) Size: 148x82x36mm Weight: 480g Peak Current: 2400A	Input: USB-C 5V/2A Output: USB-C 5V/2.1A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
507HF		Battery Capacity: 10000mAh(32Wh) Size: 122.2x164.2x46mm Weight: 711g Peak Current: 2200A	Input: 5V/2A Output: 5V/2.1A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times
577F		Battery Capacity: 10000mAh(32Wh) Size: 197x120x56mm Weight: 850g Peak Current: 2200A	Input: 5V/2A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: ≥1000 times

Economic Series

601		Battery Capacity: 10000mAh(37Wh) Size: 170x81x32mm Weight: 500g Peak Current: 1500A	Input: USB-C 5V/2.4A Output: USB1 5V/1A;USB2 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
613		Battery Capacity: 7500mAh(27.75Wh) Size: 158x85.8x27.6mm Weight: 353g Peak Current: 1200A	Input: USB-C 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A); 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
520A		Battery Capacity: 8000mAh(29.6Wh) Size: 148x82x29.5mm Weight: 320g Peak Current: 1200A	Input: USB-C 5V/2A Output: 5V/2A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
378B		Battery Capacity: 8000mAh(29.6Wh) Size: 151x80x29mm Weight: 326g Peak Current: 1200A	Input: USB-C 5V/2A Output: 5V/2.1A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
501		Battery Capacity: 10000mAh(37Wh) Size: 168x86x38.5mm Weight: 400g Peak Current: 1500A	Input: USB-C 5V/2A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
522		Battery Capacity: 10000mAh(37Wh) Size: 175x87x36mm Weight: 450g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A USB-C 5V/3A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

Advantage-03



10 Intelligent Protections, Safety Guarding

safety guarding in 360°

Advantage-04



Extremely low power consumption, No fear of battery drain

Still working ,even after storage of 2 Years

530		Battery Capacity: 10000mAh(37Wh) Size: 175x90x34mm Weight: 460g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
531		Battery Capacity: 10000mAh(37Wh) Size: 175x89x36mm Weight: 450g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
538		Battery Capacity: 10000mAh(37Wh) Size: 173.3x80x36mm Weight: 430g Peak Current: 1500A	Input: USB-C 5V/2.4A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
568		Battery Capacity: 10000mAh(37Wh) Size: 197x90.5x34.5mm Weight: 455g Peak Current: 1500A	Input: USB-C 15W 5V/3A Output: USB1 5V/1A; USB2 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
580		Battery Capacity: 12000mAh(44.4Wh) Size: 180.5x91x37mm Weight: 560g Peak Current: 1800A	Input: USB-C 5V/3A Output: USB-C PD45W;USB-A 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
510		Battery Capacity: 12000mAh(44.4Wh) Size: 190x85.8x39mm Weight: 520g Peak Current: 1800A	Input: USB-C 15W 5V/3A Output: USB1+USB2 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
529		Battery Capacity: 20000mAh(74Wh) Size: 218x85x39mm Weight: 660g Peak Current: 3000A	Input: USB-C 5V/2.4A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
386		Battery Capacity: 16000mAh(59.2Wh) Size: 225x89x30mm Weight: 564g Peak Current: 2500A	Input: USB-C 15W 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A) USB-C 15W 5V/3A;5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
387		Battery Capacity: 16000mAh(59.2Wh) Size: 224x87x39mm Weight: 540g Peak Current: 2500A	Input: USB-C 15W 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A) USB-C 15W 5V/3A;5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
163D		Battery Capacity: 20000mAh(74Wh) Size: 225x91x34mm Weight: 750g Peak Current: 3000A	Input: Quick charge(5V/2A;9V/2A) Output: 5V/1A;5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
332		Battery Capacity: 24000mAh(88.8Wh) Size: 220x102x41mm Weight: 780g Peak Current: 3250A	Input: USB-C 15W 5V/3A Output: Quick charge (5V/3A;9V/2A;12V/1.5A) 5V/2.4A; 15V/10A; USB-C 15W 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

Air Inflator Series

507		Battery Capacity: 10000mAh(37Wh) Size: 122.2x164.2x46mm Weight: 670g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.1A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
557		Battery Capacity: 10000mAh(37Wh) Size: 123x166x50mm Weight: 714g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.1A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
382		Battery Capacity: 10000mAh(37Wh) Size: 207x120x58mm Weight: 870g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
383		Battery Capacity: 10000mAh(37Wh) Size: 200x116x54mm Weight: 830g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
638		Battery Capacity: 10000mAh(37Wh) Size: 208x112x40mm Weight: 520g Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: 5V/3A Output: 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
506		Battery Capacity: 12000mAh(44.4Wh) Size: 204x122.5x58mm Weight: 1kg Peak Current: 1800A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
615		Battery Capacity: 10000mAh(37Wh) Size: 220x127x58mm Weight: 1kg Peak Current: 1500A Max Inflation Pressure: 150PSI	Input: USB-C 5V/2A Output: 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
325		Battery Capacity: 16000mAh(59.2Wh) Size: 223x123x63mm Weight: 1.5kg Peak Current: 2500A Max Inflation Pressure: 160PSI	Input: USB-C 9V/2A Output: 15V/10A; Quick charge (5V/3A;9V/2A;12V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
558A		Battery Capacity: 24000mAh(88.8Wh) Size: 230x112.5x124mm Weight: 1.7kg Peak Current: 3250A Max Inflation Pressure: 160PSI Air Flow Volume: Inflate/Deflate: 150L/min	Input: USB-C PD30W (5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Output: USB-C PD30W (5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Quick charge (5V/3A;9V/2A;12V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
558B		Battery Capacity: 12000mAh(44.4Wh) Size: 230x112.5x124mm Weight: 1.3kg Peak Current: 1800A Max Inflation Pressure: 150PSI Air Flow Volume: Inflate/Deflate: 150L/min	Input: USB-C 5V/3A Output: USB-A 5V/2.4A Operating Temp: -20°C~60°C Cycle Life: >1000 times
605		Battery Capacity: 10000mAh(37Wh) Size: 124x220x52.5mm Weight: 850g Peak Current: 1500A Max Inflation Pressure: 150PSI Air Flow Volume: Inflate/Deflate: 150L/min	Input: USB-C 5V/2A Output: 5V/2.1A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
612		Battery Capacity: 9000mAh(33.3Wh) Size: 226x74.5x40mm Weight: 470g Peak Current: 1500A Motor Power: 300W MAX Fan battery life: 92Min MAX	Input: USB-C 10W (5V/2A) Output: USB 5V/2.1A Operating Temp: -20°C~60°C Cycle Life: >1000 times Gear Settings: 4 levels (Low, Medium, High, Turbo) Fan Speed: 50 m/s MAX

Family Design Series

312		Battery Capacity: 12000mAh(44.4Wh) Size: 186x98x37mm Weight: 590g Peak Current: 1800A	Input: USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
313		Battery Capacity: 16000mAh(59.2Wh) Size: 244x105x32mm Weight: 745g Peak Current: 2500A	Input: USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD30W(5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
322		Battery Capacity: 24000mAh(88.8Wh) Size: 245x105x41mm Weight: 898g Peak Current: 3250A	Input: USB-C 5V/3A Output: Quick charge(5V/3A;9V/2A;12V/1.5A) 5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
333		Battery Capacity: 16000mAh(59.2Wh) Size: 223x93x38mm Weight: 620g Peak Current: 2500A	Input: USB-C 5V/3A Output: Quick charge(5V/3A;9V/2A;12V/1.5A) 5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
351		Battery Capacity: 24000mAh(88.8Wh) Size: 252x98x57mm Weight: 1.09kg Peak Current: 3250A	Input: USB-C PD100W(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD100W(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A) 5V/2.4A;15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
536		Battery Capacity: 10000mAh(37Wh) Size: 175x87x36mm Weight: 430g Peak Current: 1500A	Input: USB-C 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
240		Battery Capacity: 16000mAh(59.2Wh) Size: 224x89.6x36mm Weight: 625g Peak Current: 2500A	Input: USB-C 15W(5V/3A) Output: 5V/2.4A;Quick charge(5V/2.4A;9V/2A;12V/1.5A) USB-C 15W(5V/3A); 15V/10A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
241		Battery Capacity: 24000mAh(88.8Wh) Size: 224x89.6x43.8mm Weight: 775g Peak Current: 3250A	Input: USB-C 15W(5V/3A) Output: 5V/2.4A;Quick charge(5V/2.4A;9V/2A;12V/1.5A) USB-C 15W(5V/3A); 15V/10A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
528		Battery Capacity: 10000mAh(37Wh) Size: 164x84x35mm Weight: 420g Peak Current: 1500A	Input: USB-C 5V/2.4A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
600		Battery Capacity: 24000mAh(88.8Wh) Size: 223x84x35mm Weight: 750g Peak Current: 3250A	Input: USB-C 5V/2.4A Output: 5V/2.4A;12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

AC Series

183		Battery Capacity: 18000mAh(66.6Wh) Size: 224x101x34mm Weight: 830g Peak Current: 2750A AC Output:100W	Input: USB-C 9V/2A Output: Quick charge(5V/3A;9V/2A;12V/1.5A) 15V/10A; 5V/2.4A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
316		Battery Capacity: 62500mAh(225Wh) Size: 238x103x98mm Weight: 2.17kg Peak Current: 1100A AC Output:120W	Input: USB-C PD/SC100W Max(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD100W Max(5V/3A;9V/2A;12V/3A;15V/3A;20V/5A);5V/2.4A; 15V/10A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

Waterproof Series

535		Battery Capacity: 10000mAh(37Wh) Size: 184x95x31mm Weight: 505g Peak Current: 1500A IP Rating: IP65	Input: USB-C 15W 5V/3A Output: USB1+USB2 5V/3.4A; USB-C 15W 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
533		Battery Capacity: 10000mAh(37Wh) Size: 188x93x35.5mm Weight: 540g Peak Current: 1500A IP Rating: IP65	Input: USB-C 15W 5V/3A Output: USB1+USB2 5V/3.4A;USB-C 15W 5V/3A 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
590		Battery Capacity: 12000mAh(44.4Wh) Size: 177x87x38mm Weight: 550g Peak Current: 1800A	Input: USB-C PD65W Output: USB-C PD65W; Quick charge(5V/3A;9V/2A;12V/1.5A) 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
298		Battery Capacity: 20000mAh(74Wh) Size: 235x90x42mm Weight: 992g Peak Current: 3000A IP Rating: IP65	Input: USB-C PD/SC 65W (5V/3A;9V/3A;12V/3A;15V/3A;20V/3.25A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD65W (5V/3A;9V/3A;12V/3A;15V/3A;20V/3.25A);5V/2.4A; 15V/10A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times
317		Battery Capacity: 24000mAh(88.8Wh) Size: 238x105x53mm Weight: 990g Peak Current: 3250A IP Rating: IP64	Input: USB-C PD/SC 100W Max(5V/3A;9V/3A;12V/3A;15V/3A;20V/5A) Output: Quick charge(5V/3A;9V/2A;12V/1.5A) USB-C PD100W Max(5V/3A;9V/3A;12V/3A;15V/3A;20V/5A);15V/10A;5V/2.4A; 12V jump starter Operating Temp: -20°C~60°C Cycle Life: >1000 times

Super Capacitor Series

93C		Battery Capacity: 300Fx5 Size: 250x120x50mm Weight: 1.15kg Peak Current: 800A	Input: 5V/3A;12V/5A Output: 12V jump starter Operating Temp: -40°C~55°C Cycle Life: >100,000 times
161 (12V&24V)		Battery Capacity: 600Fx10 Size: 295x220x111mm Weight: 2.65kg Peak Current: 1200A	Input: 5V/3A Also suitable for 5V-1A/2A Output: 12V&24V jump starter Operating Temp: -40°C~55°C Cycle Life: >100,000 times
109A		Battery Capacity: 720Fx5 Size: 295x219x81mm Weight: 2kg Peak Current: 1200A	Input: 5V/2A;12V/10A Output: 12V jump starter Operating Temp: -40°C~55°C Cycle Life: >100,000 times