



CJS81

- LCD Screen/Jump Starter/Air Pump
- Capacity:7200mAh/10000mAh
- Start current:300A/400A
- Peak current:600A/800A



PRODUCT PARAMETERS

Features: 4 in 1 Jump Starter with Air compressor	Start current: 300A/400A
Capacity: 7200mAh/10000mAh	Peak current: 600A/800A
Type-C input: 5V/2A, 9V/2A, 12V/1.5A	Start the car: 12V
USB output: 5V/2.4A	Flashlight: Torch, Quick
Inflating Pressure: 150 PSI(MAX)	Flashing and SOS
Cylinder block diameter: 19mm	Cycle times: 1000 times
Pumping Power: 100W	Material: PC+ABS/VO
	Working temperature: -20°C-60°C



CJS76

Jump Starter with Air Compressor

- > Capacity: 7200mAh/10000mAh
- > Start Current: 300A/400A
- > Peak Current: 600A/800A



PRODUCT PARAMETERS

Features: 4 in 1 Jump Starter with Air compressor		Start current: 300A/400A
Capacity: 7200mAh/10000mAh		Peak current: 600A/800A
Specifications:		Dimension: 184*127*55mm
Type-C input: 5V/2A,9V/2A,12V/1.5A		Start the car: 12V
USB Output1&2: 5V/3A,9V/2A,12V/1.5A		Flashlight: Torch,Quick Flashing and SOS
Inflating Pressure: 150 PSI(MAX)		Cycle times: 1000 times
Cylinder block diameter: 19mm		Material: PC+ABS/VO
Pumping Power: 100W		Working temperature: -20°C-60°C



CJS78

- > Jump Starter with Air Compressor
- > Capacity: 7200mAh/10000mAh
- > Start Current: 300A/400A
- > Peak Current: 600A/800A



PRODUCT PARAMETERS

Features: 4 in 1 Jump Starter with Air compressor	Start current: 300A/400A
Capacity: 7200mAh/10000mAh	Peak current: 600A/800A
Specifications:	Dimension: 184*127*55mm
Type--C input: 5V/2A,9V/2A,12V/1.5A	Start the car: 12V
USB Output1&2: 5V/3A,9V/2A,12V/1.5A	Flashlight: Torch,Quick Flashing and SOS
Inflating Pressure: 150 PSI(MAX)	Cycle times: 1000 times
Cylinder block diameter: 19mm	Material: PC+ABS/VO
Pumping Power: 100W	Working temperature: -20°C-60°C

CJS79

- > LCD Screen/Jump Starter/Air Pump
- > Capacity: 10000mAh/12000mAh
- > Start current: 400A/500A
- > Peak current: 800A/1000A



PRODUCT PARAMETERS

Features: 4 in 1 Jump Starter with Air compressor	Start current: 400A/500A
Capacity: 10000mAh/12000mAh	Peak current: 800A/1000A
Specifications:	Start the car: 12V
Type-C input: 5V/2A, 9V/2A, 12V/1.5A	Flashlight: Torch, Quick Flashing and SOS
USB Output 1&2: 5V3A, 9V2A, 12V1.5A	Cycle times: 1000 times
Inflating Pressure: 150 PSI(MAX)	Material: PC+ABS/VO
Cylinder block diameter: 19mm	Working temperature: -20°C-60°C
Pumping Power: 100W	

CJS77

LCD Screen/PD65W Jump Starter/Air Pump
Capacity: 16000mAh
Start current: 600A
Peak current: 1200A



PRODUCT PARAMETERS

Features: Ultra 4 in 1 Jump Starter with Air compressor—PD65W	Peak current: 1200A
Capacity: 16000mAh	Charge time: Around 2 hours by PD65W input.
Specification: 3 USB ports + PD65W	Dimension: 233*124*55mm
Type—C: input/output	Start the car: 12V
(PD65W)5V/3A,9V/3A,12V/3A,15V/3A,20V/3.25A.	Flashlight: Torch,Quick
USB Output 1&2: 5V/3A,9V/2A,12V/1.5A	Flashing and SOS
Inflating Pressure: 160 PSI(MAX)	Cycle times: 1000 times
Cylinder block diameter: 22mm	Material: PC+ABS/V0
Pumping Power: 100W	Working temperature: -20℃-60℃
Start current: 600A	



CJS32

- > **Capacity:** 16000mAh/20000mAh/24000mAh
- > **Start current:** 600A/1000A/1500A
- > **Peak current:** 1200A/2000A/3000A



PRODUCT PARAMETERS

Features: LCD Screen/Big Capacity/PD65W

Peak current: 1200A/2000A/3000A

Capacity: 16000mAh/20000mAh/24000mAh

Charge time: Around 2 hours by PD65W input.

Specifications: 3 USB ports+ 1 DC port

Dimension: 243*113*66mm

Type-C: input/output (PD65W)5V/3A,9V/3A,

Start the car: 12V

12V/3A,15V/3A,20V/3.25A

Flashlight: Torch,Quick Flashing and SOS

USB/Output 1&2: 5V/3A,9V/2A,12V/1.5A

Cycle times: 1000 times

DC Output: 15V/10A

Material: PC+ABS/VO

Start current: 600A/1000A/1500A

Working temperature: -20℃-60℃



CJS33

- > Capacity: 16000mAh/20000mAh/24000mAh
- > Start current: 600A/1000A/1500A
- > Peak current: 1200A/2000A/3000A



PRODUCT PARAMETERS

Features: LCD Screen Big Capacity/PD65W

Capacity: 16000mAh/20000mAh/24000mAh

Specifications: 3 USB ports+ 1 DC port

Type-C: input/output (PD65W)5V/3A,9V/3A,

12V/3A,15V/3A,20V/3.25A

USB/Output 1&2: 5V/3A,9V/2A,12V/1.5A

DC Output: 15V/10A

Start current: 600A/1000A/1500A

Peak current: 1200A/2000A/3000A

Charge time: Around 2 hours by PD65W input

Dimension: 239.5*100*57.5mm

Start the car: 12V

Flashlight: Torch,Quick Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/VO

Working temperature: -20℃-60℃



CJS35

- > LCD Screen/Big Capacity/PD65W
- > Capacity: 16000mAh/20000mAh/24000mAh
- > Start current: 600A/1000A/1500A
- > Peak current: 1200A/2000A/3000A



PRODUCT PARAMETERS

Features: LCD Screen/Big Capacity/PD65W

Capacity: 16000mAh/20000mAh/24000mAh

Specifications: 3 USB ports+ 1 DC port

Type-C: input/output (PD65W)5V/3A,9V/3A,
12V/3A,15V/3A,20V/3.25A

USB/Output 1&2: 5V/3A,9V/2A,12V/1.5A

DC Output: 15V/10A

Start current: 600A/1000A/1500A

Peak current: 1200A/2000A/3000A

Charge time: Around 2 hours by PD65W input

Dimension: 232*108*56mm

Start the car: 12V

Flashlight Torch, Quick Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/VO

Working temperature: -20°C-60°C



CJS29

- > Capacity: 10000mAh/12000mAh
- > Start Current: 400A/500A
- > Peak Current: 800A/1000A



PRODUCT PARAMETERS

Capacity: 10000mAh/12000mAh	Peak Current: 800A/1000A
Specifications: 3 USB ports+ 1 DC port	Charge time: 300-400mins
Type-C Input: 5V/2A, 9V/2A, 12V/1.5A	Dimension: 162*84.5*33mm
USB Output1&2: 5V/3A, 9V/2A, 12V/1.5A.	Start the car: 12V
DC Output: 15V/10A	Flashlight: Torch, Quick Flashing and SOS
Start the car: 12V	Cycle times: 1000 times
Start Current: 400A/500A	Material: PC+ABS/V0
	Working temperature: -20℃ -60℃



CJS23

Capacity: 7200mAh/10000mAh
> Start Current: 300A/400A
Peak Current: 600A/800A



PRODUCT PARAMETERS

Capacity: 7200mAh/10000mAh

Charge time: 300-400mins

Specifications: 2 USB ports

Dimension: 158*84.5*33mm

Type-C Input: 5V/1.5A

Start the car: 12V

Output: 5V/2.1A

Flashlight: Torch, Quick Flashing and SOS

Start the car: 12V

Cycle times: 1000 times

Start Current: 300A/400A

Material: PC+ABS/V0

Peak Current: 600A/800A

Working temperature: -20°C-60°C




CJS28

Capacity: 7200mAh/10000mAh

> Start Current: 300A/400A

> Peak Current: 600A/800A



PRODUCT PARAMETERS

Features: IP66 Waterproof/Outdoors

Charge time: 300-400mins

Capacity: 7200mAh/10000mAh

Dimension: 158*84.5*33mm

Specifications: 2 USB ports

Start the car: 12V

Type-C Input: 5V/1.5A

Flashlight: Torch, Quick Flashing and SOS

Output: 5V/2.1A

Cycle times: 1000 times

Start the car: 12V

Material: PC+ABS/V0

Start Current: 300A/400A

Working temperature: -20°C -60°C

Peak Current: 600A/800A



CJS27

- > Capacity: 7200mAh/10000mAh
- > Start Current: 300A/400A
- > Peak Current: 600A/800A



PRODUCT PARAMETERS

Capacity: 7200mAh/10000mAh

Charge time: 300-400mins

Specifications: 2 USB ports

Dimension: 158*84.5*33mm

Type-C Input: 5V/1.5A

Start the car: 12V

Output: 5V/2.1A

Flashlight: Torch, Quick Flashing and SOS

Start the car: 12V

Cycle times: 1000 times

Start Current: 300A/400A

Material: PC+ABS/V0

Peak Current: 600A/800A

Working temperature: -20°C -60°C



CJS26

- > Capacity: 7200mAh/10000mAh
- > Start Current: 300A/400A
- > Peak Current: 600A/800A



PRODUCT PARAMETERS

Capacity: 7200mAh/10000mAh	Charge time: 300-400mins
Specifications: 2 USB ports	Dimension: 158*84.5*33mm
Type-C Input: 5V/1.5A	Start the car: 12V
Output: 5V/2.1A	Flashlight: Torch, Quick Flashing and SOS
Start the car: 12V	Cycle times: 1000 times
Start Current: 300A/400A	Material: PC+ABS/V0
Peak Current: 600A/800A	Working temperature: -20°C -60°C



CJS03

- > Capacity: 7200mAh
- > Start Current: 300A
- > Peak Current: 600A



PRODUCT PARAMETERS

Features: IP66 Waterproof/Outdoors

Capacity: 7200mAh

Specifications: 2 USB ports

Micro Input: 5V/1.5A

Output: 5V/2.1A

Start the car: 12V

Start Current: 300A

Peak Current: 600A

Charge time: 300-400mins

Dimension: 140*85*27mm

Start the car: 12V

Flashlight: Torch, Quick

Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/VO

Working temperature: -20°C -60°C



CJS05

- > Capacity: 7200mAh
- > Start Current: 300A
- > Peak Current: 600A



PRODUCT PARAMETERS

Features: IP66 Waterproof

/Outdoors Jump Starter

Capacity: 7200mAh

Specifications: 2 USB ports

Micro Input: 5V/1.5A

Output: 5V/2.1A

Start the car: 12V

Start Current: 300A

Peak Current: 600 A

Charge time: 300-400mins

Dimension: 140*85*27mm

Start the car: 12V

Flashlight: Torch, Quick Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20°C -60°C



CJS11

- > IP66 Waterproof/Outdoors Jump Starter
- > Capacity: 7200mAh/10000mAh
- > Start Current: 300A/400A
- > Peak Current: 600A/800A



PRODUCT PARAMETERS

Features: IP66 Waterproof

/Outdoors Jump Starter

Capacity: 7200mAh/10000mAh

Specifications: 2 USB ports

Micro Input: 5V/1.5A

Output: 5V/2.1A

Start the car: 12V

Start Current: 300A/400A

Peak Current: 600A/800A

Charge time: 300-400mins

Dimension: 158*88*33mm

Start the car: 12V

Flashlight: Torch, Quick Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20°C -60°C

CJS12



PRODUCT PARAMETERS

Features: IP66 Waterproof	Peak Current: 600A/800A
/Outdoors Jump Starter	Charge time: 300-400mins
Capacity: 7200mAh/10000mAh	Dimension: 158*88*33mm
Specifications: 2 USB ports	Start the car: 12V
Micro Input: 5V/1.5A	Flashlight: Torch, Quick Flashing and SOS
Output: 5V/2.1A	Cycle times: 1000 times
Start the car: 12V	Material: PC+ABS/V0
Start Current: 300A/400A	Working temperature: -20°C -60°C

CJS15



PRODUCT PARAMETERS

Features: IP66 Waterproof	Peak Current: 600A/800A
/Outdoors Jump Starter	Charge time: 300-400mins
Capacity: 7200mAh/10000mAh	Dimension: 158*88*33mm
Specifications: 2 USB ports	Start the car: 12V
Micro Input: 5V/1.5A	Flashlight: Torch, Quick Flashing and SOS
Output: 5V/2.1A	Cycle times: 1000 times
Start the car: 12V	Material: PC+ABS/V0
Start Current: 300A/400A	Working temperature: -20°C -60°C

CJS02



PRODUCT PARAMETERS

Features: IP68 Waterproof

/Outdoors Jump Starter

Capacity: 10000mAh

Specifications: 4 USB ports

Micro Input: 5V/2A

Type-C Input: 5V/2A

Output1&2: 5V/3A,9V/2A,12V/1.5A

Start the car: 12V

Start Current: 400A

Peak Current: 800A

Charge time: 300-400mins

Dimension: 168*92*38mm

Start the car: 12V

Flashlight: Torch,Quick

Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20°C -60°C

CJS08



PRODUCT PARAMETERS

Features: IP67 Waterproof

/Outdoors Jump Starter

Capacity: 10000mAh

Specifications: 4 USB ports

Micro Input: 5V/2A

Type-C Input: 5V/2A

Output1&2: 5V/3A,9V/2A,12V/1.5A

Start the car: 12V

Start Current: 400A

Peak Current: 800A

Charge time: 300-400mins

Dimension: 178*98*43mm

Start the car: 12V

Flashlight: Torch,Quick

Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20°C -60°C

CJS06



PRODUCT PARAMETERS

Features: IP67 Waterproof /Outdoors Jump Starter	Peak Current: 1000A
Capacity: 12000mAh	Charge time: 300-400mins
Specifications: 4 USB ports	Dimension: 184*92*41mm
Micro Input: 5V/2A	Start the car: 12V
Type-C Input: 5V/2A	Flashlight: Torch, Quick
Output1&2: 5V/3A, 9V/2A, 12V/1.5A	Flashing and SOS
Start the car: 12V	Cycle times: 1000 times
Start Current: 500A	Material: PC+ABS/V0
	Working temperature: -20°C-60°C

CJS07



PRODUCT PARAMETERS

Features: IP67 Waterproof /Outdoors Jump Starter	Peak Current: 1000A
Capacity: 12000mAh	Charge time: 300-400mins
Specifications: 4 USB ports	Dimension: 184*100*46mm
Micro Input: 5V/2A	Start the car: 12V
Type-C Input: 5V/2A	Flashlight: Torch, Quick
Output1&2: 5V/3A, 9V/2A, 12V/1.5A	Flashing and SOS
Start the car: 12V	Cycle times: 1000 times
Start Current: 500A	Material: PC+ABS/V0
	Working temperature: -20°C-60°C

CJS09



PRODUCT PARAMETERS

Features: IP67 Waterproof /Outdoors Jump Starter	Peak Current: 1200A
Capacity: 16000mAh	Charge time: 400-500mins
Specifications: 4 USB ports	Dimension: 185*100*45mm
Micro Input: 5V/2A	Start the car: 12V
Type-C Input: 5V/2A	Flashlight: Torch,Quick Flashing and SOS
Output1&2: 5V/3A,9V/2A,12V/1.5A	Cycle times: 1000 times
Start the car: 12V	Material: PC+ABS/V0
Start Current: 600A	Working temperature: -20°C-60°C

CJS16



PRODUCT PARAMETERS

Features: IP67 Waterproof/ Outdoors Jump Starter	Start Current: 600A
Capacity: 16000mAh	Peak Current: 1200A
Specifications: 4 USB ports	Charge time: 400-500mins
Micro Input: 5V/2.1A	Dimension: 185*100*45mm
Type-C:Input/output(PD30W): 5V/3A,9V/3A,12V/2.5A,20V/1.5A& (QC18W)5V/3A,9V/2A,12V/1.5A.	Start the car: 12V
Output1&2: 5V/3A,9V/2A,12V/1.5A.	Flashlight: Torch,Quick Flashing and SOS
Start the car: 12V	Cycle times: 1000 times
	Material: PC+ABS/V0
	Working temperature: -20°C-60°C

CJS10



PRODUCT PARAMETERS

Features: IP67 Waterproof

/Outdoors Jump Starter

Capacity: 16000mAh

Specifications: 4 USB ports

Micro Input: 5V/2.1A

Type-C: Input/output(PD30W):

5V/3A,9V/3A,12V/2.5A,20V/1.5A&

(QC18W)5V/3A,9V/2A,12V/1.5A.

Output1&2: 5V/3A,9V/2A,12V/1.5A.

Start the car: 12V

Start Current: 600A

Peak Current: 1200A

Charge time: 400-500mins

Dimension: 194*98*43mm

Start the car: 12V

Flashlight: Torch,Quick Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20℃-60℃

CJS18



PRODUCT PARAMETERS

Features: IP67 Waterproof

/Outdoors Jump Starter

Capacity: 16000mAh

Specifications: 4 USB ports

Micro Input: 5V/2.1A

Type-C: Input/output(PD30W):

5V/3A,9V/3A,12V/2.5A,20V/1.5A&(QC18W)

5V/3A,9V/2A,12V/1.5A.

Output1&2: 5V/3A,9V/2A,12V/1.5A.

Start the car: 12V

Start Current: 600A

Peak Current: 1200A

Charge time: 400-500mins

Dimension: 194*98*43mm

Start the car: 12V

Flashlight: Torch,Quick Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20℃-60℃



CJS19

- > **Capacity: 16000mAh**
- > **Start Current: 600A**
- > **Peak Current: 1200A**



PRODUCT PARAMETERS

Features: IP67 Waterproof

/Outdoors Jump Starter

Capacity: 16000mAh

Specifications: 4 USB ports

Micro Input: 5V/2.1A

Type-C: Input/output(PD30W)

5V/3A,9V/3A,12V/2.5A,20V/1.5A&(QC18W)

5V/3A,9V/2A,12V/1.5A.

Output1&2: 5V/3A,9V/2A,12V/1.5A.

Start the car: 12V

Start Current: 600A

Peak Current: 1200A

Charge time: 400-500mins

Dimension: 185*100*45mm

Flashlight: Torch,Quick

Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20°C-60°C

CJS30



PRODUCT PARAMETERS

Features: IP66 Waterproof

Wireless Charging

Capacity: 12000mAh

Specifications: 2 USB ports

+Wireless Charging

Type-C input: 5V/2A

USB output: 5V/3A,9V/2A,12V/1.5A

Wireless Charger: 5V/2A,10W MAX

Start the car: 12V

Start Current: 500A

Peak Current: 1000A

Charge time: 400-500mins

Dimension: 180*92*36mm

Flashlight: Torch,Quick

Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20°C -60°C

CJS31



PRODUCT PARAMETERS

Features: IP66 Waterproof

Wireless Charging

Capacity: 12000mAh

Specifications: 2 USB ports

+Wireless Charging

Type-C input: 5V/2A

USB output: 5V/3A,9V/2A,12V/1.5A

Wireless Charger: 5V/2A,10W MAX

Start the car: 12V

Start Current: 500A

Peak Current: 1000A

Charge time: 400-500mins

Dimension: 180*92*36mm

Flashlight: Torch,Quick

Flashing and SOS

Cycle times: 1000 times

Material: PC+ABS/V0

Working temperature: -20°C -60°C

CJS72



PRODUCT PARAMETERS

Features: Jump Starter with air compressor	Start the car: 12V
Capacity: 16000mAh	Start current: 600A
Specifications:	Peak current: 1200A
Type-C input: 5V/2A, 9V/2A, 12V/1.5A	Flashlight: Torch, Quick Flashing and SOS
USB output1&2: 5V/3A, 9V/2A, 12V/1.5A	Cycle times: 1000times
DC output: 15V/8A	Charge time: 250-400mins
Inflating pressure: 150 PSI (MAX)	Material: PC+ABS/V0
Cylinder block diameter: 25mm	Working temperature: -20°C -60°C
Pumping Power: 120W	

CJS73



PRODUCT PARAMETERS

Features: Jump Starter with air compressor	Start the car: 12V
Capacity: 16000mAh	Start current: 600A
Specifications:	Peak current: 1200A
Type-C input: 5V/3A, 12V/1.5A	Flashlight: Torch, Quick Flashing and SOS
USB output1&2: 5V/2A, 9V/2A, 12V/1.5A	Cycle times: 1000times
DC output: 15V/8A	Charge time: 250-400mins
Inflating pressure: 150 PSI (MAX)	Material: PC+ABS/V0
Cylinder block diameter: 25mm	Working temperature: -20°C -60°C
Pumping Power: 120W	

Smart Protection Clamp

8 Protection Features



Short Circuit Protection



Overload Protection



Low Voltage Protection



Overvoltage Protection



Overcharge & Overdischarge Protection



Temperature Protection



Reverse Charging Protection



Reverse Connection Protection

